

1. PRODUCT NAME

CBA (Cove Base Adhesive)

2. MANUFACTURER

PROFLEX® Products, Inc.
2826 Broadway Center Blvd
Brandon, Florida 33510
Telephone: 863-937-9623
Toll Free: 877-577-6353
Fax: 863-937-9624
Internet: www.proflex.us



3. PRODUCT DESCRIPTION

PROFLEX® Cove Base Adhesive (CBA) is a premium solvent free adhesive with fast, aggressive wet suction to grip rubber and vinyl wall base. PROFLEX® CBA can be used over most interior wall surfaces with the exception of vinyl wall covering and other similar non-porous surfaces that prevent the curing of any latex-based adhesive.

PROFLEX® CBA is LEED compliant and is also compliant with South Coast Air Quality Management District Rule 1168.

PROFLEX® CBA qualifies for the Carpet & Rug Institutes Green Label Plus Program. This is a third party certification with the most stringent VOC regulations in the country.

Advantages

- VOC Compliant
- Easy water clean-up
- Strong bond
- For all vinyl & rubber cove base
- Easy to apply

Suitable Substrates

- Porous Concrete
- Properly Prepared Gypsum
- APA Approved Plywood
- Drywall
- Fully Cured Masonry Walls

Packaging 30 fl. Oz / 887 ML, approximately 55-60 linear feet of 4" base per 30 oz. Tube.

Cautions and Limitations

- For interior installations only.
- Do not install when ambient temperatures is not between 60°F - 95°F.
- Do not install when ambient relative humidity is above 65%.
- It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the user's intended use.

4. TECHNICAL DATA

Technical Data	
Base Polymer	Acrylic Polymer
Color	Light Straw
Solids	54-59%
VOC Content	<1 gram per liter
pH	9.3
Consistency	Paste
Trowel Ability	Light, easy
Shelf Life	One year in unopened container
Storage	40°F-95°F
Application Temperature	65°F-95°F (18°C-35°C)
Open Time	Up to 30 minutes
Freeze Thaw Stability	5 cycles @ 20°F

5. INSTALLATION

1. Adhesive, wall base and job site must be conditioned at 65°F - 80°F for 48 hours before and after installation.
2. Use only on structurally sound surfaces, dry wall, concrete block, brick, plywood, paneling, masonry, plaster, etc.
3. Apply to surfaces that are clean, dry and free from dust, wax and grease. Remove loose paint, plaster, old adhesive and other contaminants that would interfere with adhesion.
4. Cement or plaster must be thoroughly seasoned and dry.
5. With a 1/8" square or V-notched spreader, spread on back of base or wall surface.
6. Press base firmly into place immediately after application of adhesive.
7. Wrapped base or rolled base should lay flat for 24 hours before application.
8. For best results, it is recommended to wipe the back of rubber wall base with Mineral Spirits to remove residual mold release from manufacture.

Clean-up

Remove wet adhesive immediately with a damp cloth. Use mineral spirits to remove dried adhesive. CAUTION: Mineral Spirits are flammable. Read and follow all precautions on container label.

DO NOT APPLY OVER NON-POROUS SURFACES SUCH AS MASONITE, PLASTIC LAMINATES OR VINYL WALL COVERINGS.

6. AVAILABILITY

PROFLEX® Products are available nationwide.

To locate PROFLEX® products in your area, please contact:

Phone: 877-577-6353

Website: www.proflex.us

7. WARRANTY

Contact PROFLEX® Technical Services for specific warranty information.

8. MAINTENANCE

None required, but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. TECHNICAL SERVICES

Technical assistance

Information is available by calling the Technical Support

Toll Free: 877-577-6353

Fax: 863-937-9624

Technical and safety literature

To acquire technical and safety literature, please visit our website www.proflex.us

10. FILING SYSTEM

Division 9