

# PROFLEX

## PENETRATING SEALER

### PROFESSIONAL GRADE SEALERS, CARE and MAINTENANCE PRODUCTS

#### PENETRATING SEALER PS61

A water based penetrating sealer designed for the protection of all porous surfaces including grout, tile, natural stone, quartz, engineered stone, terrazzo, concrete, quarry tile, ceramic tile, porcelain tile, brick & masonry surfaces. Ideal for both interior and exterior applications and is non-flammable and V.O.C. compliant.

#### ADVANTAGES

- Water Based
- Non-Flammable
- Easy to use
- Natural Look Finish
- Resistant to Moisture
- Protection from stains
- No Hazardous fumes
- Interior / Exterior Use

#### SUITABLE SURFACES AND COVERAGES

- Grout
- Natural Stone
- Quartz
- Engineered Stone
- Terrazzo
- Concrete
- Quarry Tile
- Ceramic / Porcelain Tile
- Brick and Masonry Surfaces

COVERAGE (500—3000 -per 1 gallon of product)

**NOT RECOMMENDED FOR** Impervious surfaces, glass, metal, glazed ceramic tile, wood, or fabric. Not for use below water line. Not for use as an oil repellent.

#### INSTALLATION INSTRUCTIONS:

**SAMPLE TESTING:** Due to variations between substrates, sample testing is recommended to assure maximum performance and suitability for intended use. Minimal shading may occur. User must determine the suitability of the product for its intended use.

**IMPORTANT:** Read entire label, Product Data Sheet, and MSDS before using product. Use directly from container. Do NOT – under any circumstance – thin or dilute. Protect exposed surfaces including wood, carpet, metal & landscaping. Use Proflex cleaning products to assure surface is clean and prepared for application and ongoing care and maintenance.

**DIRECTIONS:** SHAKE CONTAINER BEFORE USE.

- 1) Apply Penetrating Sealer evenly to surface until damp using a clean white cotton towel, paint roller or paint brush.
  - 2) Leave on surface for 3 – 5 minutes for maximum penetration before removing all excess product with a clean white towel before it dries. Any excess product “residue” that may dry on the surface can be removed by applying water and buffing with a soft nylon pad. A second application may be necessary for some surfaces. Allow 24 – 72 hours to fully cure.
- GROUT RELEASE:** Penetrating Sealer can be used as a grout release for new installations. Follow steps 1 – 2, being careful not to saturate open grout joints and allow at least 6 – 12 hours before grouting.

**CAUTION:** Ensure product containers are kept closed when not in use and store in a cool, dry, area. Keep out of reach of children and pets. **FIRST AID:** Skin, wash thoroughly affected area with soap and water. Eyes, wash for 15 minutes with water and immediately seek medical attention. Ingestion, Seek immediate medical attention. Do not induce vomiting unless directed by a physician.

**FOR 24 HOUR EMERGENCY:** CONTACT CHEMTEL 1-800-255-3294



#### PACKAGING

One US Gallon Containers,  
One US Quart Containers,